

30

Amendments to the Claims:

This listing of Claims will replace all prior versions and listings of claims in the application. Each claim has a status indicator selected from the group of seven (7) permissible status indicators, as indicated:

35

- Original;
- Currently Amended;
- Canceled;
- Withdrawn;
- Previously Presented;
- New; or
- Not entered

40

The application was filed with original Claims 1-52.

Claims 1-52 are pending in the application.

45

Claims 5-8, 13, 14, 18, 23, 24, 48, and 52 are objected to, but are indicated to be allowable if rewritten in independent form to include all the limitations of the base claim and any intervening claim. Accordingly, appropriate ones of these Claims are so rewritten in independent form as the Examiner suggests. Thus, the indicated Claims are respectfully submitted to be ready for allowance.

50

Claim 49 is indicated to be allowable.

Original Claims 27, 32, and 39 are canceled.

Original Claims 5, 13, 15, 16, 18, 23, 25, 26, 28, 31, 33, 36, 38, 40, 48, and 52 are presently amended.

55

60

Listing of Claims:

65 1.(Original) A high-volume, high-utility, non-conductive enclosure for electrical
components and wiring comprising: a molded polymer junction box including a non-perforate
back wall, and plural non-perforate contiguous walls extending generally perpendicularly to said
back wall, and each one of said plural contiguous walls joining integrally to the back wall and
also to adjacent ones of said plural contiguous walls, said back wall and said plural contiguous
70 walls cooperatively defining a chamber within said junction box, with said plural contiguous
walls at respective end edges cooperatively forming an opening to said chamber, at least one of
said plural contiguous walls carrying an integral mounting lug member extending across said
opening, and said mounting lug member also extending inwardly of said chamber from
substantially said end edge of said at least one wall toward but short of said back wall to define a
75 termination surface, whereby an electrical component may be inserted via said opening into said
chamber to be secured within the junction box at said mounting lug.

2. (Original) The enclosure of Claim 1 wherein said one wall defines a wall portion
extending from said termination surface to said back wall, whereby said wall portion provides a
wall surface within said junction box for receiving a conduit socket.

3. (Original) The enclosure of Claim 2 wherein at least a selected one of said plural
contiguous walls carries on an outer surface thereof a drilling indicia for positioning a conduit
socket.

4. (Original) The enclosure of Claim 3 wherein said at least selected one of said plural
contiguous walls carries plural drilling indicia, and each one of said plural drilling indicia are
further spaced from each of: an inner surface of said back wall, and from an inner surface of an
adjacent one of said plural contiguous walls by a determined distance, and are spaced from an
5 adjacent drilling indicia by twice said determined distance.

5. (Currently amended) A high-volume, high-utility, non-conductive enclosure for electrical components and wiring comprising: a molded polymer junction box including a non-perforate back wall, and plural non-perforate contiguous walls extending generally perpendicularly to said back wall, and each one of said plural contiguous walls joining integrally to the back wall and also to adjacent ones of said plural contiguous walls, said back wall and said plural contiguous walls cooperatively defining a chamber within said junction box, with said plural contiguous walls at respective end edges cooperatively forming an opening to said chamber, at least one of said plural contiguous walls carrying an integral mounting lug member extending across said opening, and said mounting lug member also extending inwardly of said chamber from substantially said end edge of said at least one wall toward but short of said back wall to define a termination surface, whereby an electrical component may be inserted via said opening into said chamber to be secured within the junction box at said mounting lug;

wherein said one wall defines a wall portion extending from said termination surface to said back wall, whereby said wall portion provides a wall surface within said junction box for receiving a conduit socket;

wherein at least a selected one of said plural contiguous walls carries on an outer surface thereof a drilling indicia for positioning a conduit socket;

wherein said at least selected one of said plural contiguous walls carries plural drilling indicia, and each one of said plural drilling indicia are further spaced from each of: an inner surface of said back wall, and from an inner surface of an adjacent one of said plural contiguous walls by a determined distance, and are spaced from an adjacent drilling indicia by twice said determined distance; ~~The enclosure of Claim 4~~

further including a nut member threadably engageable with a conventional conduit socket member, said nut member providing plural flats each substantially at a radius of said determined distance, and which plural flats when said nut member is centered substantially at one of said plural drilling indicia are engageable with one of: said inner surface of said back wall, with said inner surface of an adjacent one of said plural contiguous walls, or with a confronting flat of an adjacent nut member which is also centered at an adjacent drilling indicia; whereby, said nut member engages one or more of said inner wall surfaces and another nut member to substantially

30 prevent said nut member from rotating when a conduit socket member is tightened into said nut member.

6. (Original) The enclosure of Claim 5 wherein said nut member comprises:

a nut member body of injection molded plastic, the nut member body internally defining a through bore, and externally defining surface features allowing the nut member body to be grasp with a gripping or wrenching tool;

5 said nut member body also defining within said through bore a single female helical thread having circumferentially opposite thread ends, said opposite thread ends being spaced slightly from one another circumferentially and not overlapping one another in the circumferential direction so as to define an axially extending gap

7. (Original) The enclosure of Claim 6 wherein said nut member external surface features include plural wrenching flats.

8. (Original) The enclosure of Claim 6 wherein said nut member external surface features include plural axially extending ribs.

9. (Original) The enclosure of Claim 1 wherein said mounting lug cantilevers from said at least one of said plural contiguous walls.

10. (Original) The enclosure of Claim 9 wherein said at least one of said plural contiguous walls carries plural mounting lugs integrally joining with said at least one wall.

11. (Original) The enclosure of Claim 10 wherein said plural mounting lugs each cantilevers from said one of said plural contiguous walls.

12. (Original) The enclosure of Claim 11 wherein each of said plural mounting lugs is independent of each other mounting lug of said plural mounting lugs.

- 13.(Currently amended) A high-volume, high-utility, non-conductive enclosure for electrical components and wiring comprising: a molded polymer junction box including a non-perforate back wall, and plural non-perforate contiguous walls extending generally perpendicularly to said back wall, and each one of said plural contiguous walls joining integrally to the back wall and also to adjacent ones of said plural contiguous walls, said back wall and said plural contiguous walls cooperatively defining a chamber within said junction box, with said plural contiguous walls at respective end edges cooperatively forming an opening to said chamber, at least one of said plural contiguous walls carrying an integral mounting lug member extending across said opening, and said mounting lug member also extending inwardly of said chamber from substantially said end edge of said at least one wall toward but short of said back wall to define a termination surface, whereby an electrical component may be inserted via said opening into said chamber to be secured within the junction box at said mounting lug;
- 5
- wherein said mounting lug cantilevers from said at least one of said plural contiguous walls;
- 10
- wherein said at least one of said plural contiguous walls carries plural mounting lugs integrally joining with said at least one wall;
- 15
- wherein said plural mounting lugs each cantilevers from said one of said plural contiguous walls; ~~The enclosure of Claim 11~~
- 20 further including an elongate web member extending transversely of said junction box, and said web member integrally joining with each of said plural mounting lugs.

14. (Original) The enclosure of Claim 13 wherein said web member has a pair of opposite ends, and said web member further joins integrally at each of its opposite ends with respective ones of said plural contiguous walls.

15. (Currently amended) A molded non-conductive plastic junction box comprising a non-perforate back wall and four contiguous non-perforate integral side walls each joined both to the back wall and to two adjacent ones of the four contiguous side walls, said four contiguous side walls being disposed in spaced apart opposite pairs, said back wall and four side walls
- 5 cooperatively bounding a chamber within said junction box, and each side wall terminating at an end edge substantially in a common plane to cooperatively define an opening to said chamber,

and one of said four contiguous side walls carrying an integral mounting lug extending from said one side wall toward the opposite one of said side walls, said mounting lug also extending from substantially said common plane toward but short of said back wall, and said one wall providing
10 a wall portion extending from said mounting lug to said back wall which is unobstructed and available for mounting of a conduit socket therein, whereby said junction box provides increased interior volume and increased wall area for the mounting of conduit sockets.

16. (Currently amended) The junction box of Claim 15 wherein because each of said back wall and said four side walls are non-perforate, whereby said back wall and each of said four side walls each have no openings through which to connect a conduit socket, whereby the full area of said back wall and said four side walls is available so that a user can make one or
5 more holes where desired in said walls in order to mount one or more conduit sockets on said junction box where desired.

17. (Original) The junction box of Claim 15 wherein at least one of said four side walls includes outwardly disposed drilling indicia, said drilling indicia being spaced from an inside surface of said back wall, and from an inside surface of an adjacent one of said four side walls by a determined distance.

18. (Currently amended) A molded non-conductive plastic junction box comprising a back wall and four contiguous integral side walls each joined both to the back wall and to two adjacent ones of the four contiguous side walls, said four contiguous side walls being disposed in spaced apart opposite pairs, said back wall and four side walls cooperatively bounding a chamber
5 within said junction box, and each side wall terminating at an end edge substantially in a common plane to cooperatively define an opening to said chamber, and one of said four contiguous side walls carrying an integral mounting lug extending from said one side wall toward the opposite one of said side walls, said mounting lug also extending from substantially said common plane toward but short of said back wall, and said one wall providing a wall
10 portion extending from said mounting lug to said back wall which is unobstructed and available for mounting of a conduit socket therein, whereby said junction box provides increased interior volume and increased wall area for the mounting of conduit sockets;

wherein at least one of said four side walls includes outwardly disposed drilling indicia, said drilling indicia being spaced from in inside surface of said back wall, and from an inside surface of an adjacent one of said four side walls by a determined distance; ~~The junction box of Claim 17~~

further including a nut member threadably engageable with a conventional conduit socket member, said nut member providing plural flats each substantially at a radius of said determined distance, and which plural flats when said nut member is centered substantially at one of said plural drilling indicia are engageable with one of: said inner surface of said back wall, with said inner surface of an adjacent one of said four side walls, or with a confronting flat of an adjacent nut member which is also centered at an adjacent drilling indicia; whereby, said nut member engages one or more of said inner side wall surfaces and another adjacent nut member to substantially prevent said nut member from rotating when a conduit socket member is tightened into said nut member.

19. (Original) The junction box of Claim 15 wherein said mounting lug cantilevers from said one of said four side walls.

20. (Original) The junction box of Claim 19 wherein said one side wall carries plural mounting lugs integrally joining with said one side wall.

21. (Original) The junction box of Claim 20 wherein said plural mounting lugs each cantilevers from said one side wall.

22. (Original) The junction box of Claim 21 wherein each of said plural mounting lugs is independent of each other mounting lug of said plural mounting lugs on said one side wall.

23. (Currently amended) A molded non-conductive plastic junction box comprising a back wall and four contiguous integral side walls each joined both to the back wall and to two adjacent ones of the four contiguous side walls, said four contiguous side walls being disposed in spaced apart opposite pairs, said back wall and four side walls cooperatively bounding a chamber within said junction box, and each side wall terminating at an end edge substantially in a

common plane to cooperatively define an opening to said chamber, and one of said four contiguous side walls carrying an integral mounting lug extending from said one side wall toward the opposite one of said side walls, said mounting lug also extending from substantially said common plane toward but short of said back wall, and said one wall providing a wall portion extending from said mounting lug to said back wall which is unobstructed and available for mounting of a conduit socket therein, whereby said junction box provides increased interior volume and increased wall area for the mounting of conduit sockets;

wherein said mounting lug cantilevers from said one of said four side walls;

wherein said one side wall carries plural mounting lugs integrally joining with said one side wall;

wherein said plural mounting lugs each cantilevers from said one side wall; The junction box of Claim 21

further including an elongate web member extending transversely of said junction box, and said web member integrally joining with each of said plural mounting lugs on said one side wall.

24. (Original) The junction box of Claim 23 wherein said web member has a pair of opposite ends, and said web member further joins integrally at each of its opposite ends with a side wall extending angularly to said one side wall.

25. (Currently amended) A method of providing a non-conductive plastic junction box with conduit sockets which may be located on said junction box substantially anywhere a user chooses, said method comprising steps of

providing the junction box with a non-perforate integral back wall having a periphery and at least ~~four~~ one contiguous non-perforate integral side walls ~~each joined both joining~~ joining to the back wall ~~and to two adjacent ones of the at least four contiguous side walls~~ at said periphery thereof;

~~disposing said at least four contiguous side walls in spaced apart opposite pairs;~~

utilizing said back wall and said at least ~~four~~ one contiguous side walls to cooperatively bound a chamber within said junction box;

10 providing ~~and each of~~ said at least ~~four~~ one side walls with a terminating end edge substantially everywhere in a common plane, and employing said end edges to ~~cooperatively~~ define an opening to said chamber;

providing on ~~one of~~ said at least ~~four~~ one contiguous side walls an integral mounting lug extending from ~~said one side of said opening wall~~ toward but short of the opposite ~~one side~~ of
15 said ~~side walls~~ opening and from substantially said common plane toward but short of said back wall to terminate at a termination surface spaced from said back wall; and

inwardly of said mounting lug termination surface, utilizing said one side wall to provide a wall portion extending from ~~inwardly~~ said termination surface of said mounting lug to said back wall, which wall portion is unobstructed and available for mounting of a conduit socket
20 therein;

whereby said junction box provides both increased interior volume and increased side wall area for the mounting of conduit sockets at holes formed therein by a user of the junction box.

26. (Currently amended) An electrical junction box having plural walls cooperatively arranged and interconnected so as to substantially bound a volume and to define an opening to said volume by which electrical components and electrical wiring may pass into and from said volume; at least one wall of said plural walls of said junction box defining an insert
5 recess opening outwardly from said volume, said insert recess having an outer portion of a larger size opening outwardly on said junction box and an inner portion of a smaller size opening inwardly to said volume, and said portions cooperatively defining both an outwardly disposed shoulder along said insert recess and a passage opening outwardly on said junction box as well as to said volume, whereby said insert recess may receive into said larger sized outer portion a
10 matchingly configured insert member seating upon said shoulder and ~~which provides~~ providing at least one conduit socket for joining to said junction box of receiving an end termination portion of at least one electrical conduit ~~at an end termination portion thereof~~.

27. (Canceled) The junction box of Claim 26 wherein said insert recess includes a larger sized portion opening outwardly on said junction box, and a smaller sized portion opening inwardly of said junction box to said volume, said larger sized portion and said smaller sized

portion communicating with one another to provide an outwardly disposed shoulder within said
5 insert recess.

28. (Currently amended) The junction box of Claim 26 wherein said insert recess has
a selected shape in axial view along said passage.

29. (Original) The junction box of Claim 28 wherein said selected shape is selected from
the group consisting of: rectangular, square, oval, semicircular, and bi-cameral.

30. (Original) The junction box of Claim 29 wherein said selected shape is bi-cameral,
and is symmetrical in axial view and includes a pair of semicircular recess portions arranged in
mirror image to one another.

31. (Currently amended) A method of providing an electrical junction box, said
method comprising steps of:

providing plural walls for said junction box, and cooperatively arranging and
interconnecting said plural walls so as to substantially bound a volume;

5 utilizing an end edge of selected ones of said plural walls to cooperatively define an
opening to said volume by which electrical components and electrical wiring may pass into and
from said volume;

utilizing at least one wall of said plural walls of said junction box to define an insert
recess, and configuring said insert recess to open outwardly from said volume outwardly on said
10 junction box, and to provide a larger sized outer portion, and a smaller sized inner portion
cooperating with said larger portion to define an outwardly disposed shoulder along said insert
recess, whereby said insert recess may receive a matchingly configured insert member into said
larger portion and seating upon said shoulder and defining a conduit socket which providing
provides for joining to said junction box of at least one electrical conduit.

32. (Canceled) The method of Claim 31 further including the steps of providing for said
insert recess to include a larger sized portion opening outwardly on said junction box, and a
smaller sized portion opening inwardly of said junction box to said volume, and utilizing said

larger sized portion and said smaller sized portion to provide an outwardly disposed shoulder
5 within said insert recess.

33. (Currently amended) The method of Claim ~~32~~ 31 further including the step of providing for said insert recess to have a selected shape in axial view of said insert recess.

34. (Original) The method of Claim 33 including the step of selecting said selected shape from the group consisting of: rectangular, square, oval, semicircular, and bi-cameral.

35. (Original) The method of Claim 34 including the step of choosing said selected shape to be bi-cameral, and configuring said bi-cameral shape to be symmetrical in axial view and to include a pair of semicircular recess portions arranged in mirror image to one another.

36. (Currently amended) An unitary insert member for use in combination with an electrical junction box, said insert member including an axially extending cylindrical body portion of selected configuration in axial end view, and at least one boss member extending axially from said body portion, said body portion and said boss member cooperatively defining a
5 stepped axial through bore with a larger diameter portion opening outwardly on said boss member and a smaller diameter portion ~~extending axially in said boss member and body portion~~ and opening ~~on through~~ said body portion and cooperating with said larger diameter portion to define a shoulder on said through bore disposed toward said larger diameter portion, said stepped through bore providing a socket for receiving into said larger diameter portion an end portion of
10 an electrical conduit.

37. (Original) The insert member of Claim 36 wherein said insert member provides a pair of boss members and a corresponding pair of conduit sockets in side by side relationship.

38. (Currently amended) The insert member of Claim 36 wherein said body portion has an axial center line in side elevation view, and said boss portion similarly has an axial center line in side elevation view, and the respective axial centerlines of said body portion and of said

boss member are parallel to one another and are offset laterally of said centerlines relative being
5 in a selected relationship to one another.

39. (Canceled) The insert member of Claim 38 wherein said selected relationship of said centerlines of said boss member and of said body portion is selected from the group consisting of: substantially aligned with one another in side elevation view, and offset from one another by a determined amount in side elevation view.

40. (Currently amended) An insert member for use in combination with a pair of electrical junction boxes each of which defines a respective one of a pair of outwardly opening insert recesses each of rectangular shape in axial view of said pair of insert recesses, said insert member providing for joining of said pair of electrical junction box ~~in~~ to form a ganged pair ~~or~~
5 plurality of junction boxes, said insert member including a central body portion ~~of selected configuration in end view~~, and a pair of rectangular boss members matching in size and shape with said pair of insert recesses and extending in opposite directions from said body portion, said body portion and said pair of boss members cooperatively defining a rectangular through passage opening outwardly on each of said pair of boss members and extending axially ~~in said boss~~
10 ~~members and body portion~~ through said insert member, whereby each one of said pair of boss members is received into a respective insert recess of said pair of junction boxes to form a ganged pair of junction boxes and said rectangular through passage provides for passage of electrical wires between said ganged pair of junction boxes.

41. (Original) The insert member of Claim 40 wherein said through passage is generally rectangular in axial view.

42. (Original) A conduit coupling defining a pair of oppositely extending conduit sockets each providing for adhesively receiving an end portion of a run of conduit, said conduit coupling further including an exterior boss providing a mounting surface extending parallel to the axis of the coupling, and provision for receiving and retaining a spacer member disposed between said
5 exterior boss and a surface upon which said conduit coupling is attached.

43. (Original) The conduit coupling of Claim 42 wherein said provision at said boss includes a pair of parallel mounting pins.

44. (Original) The conduit coupling of Claim 43 wherein said pair of parallel mounting pins each define one or more clipping necks at which the length of the pins may be conveniently shortened by cutting or clipping.

45. (Original) The conduit coupling of Claim 42 and further a tab member including a pair of holes spaced apart to match with and be received over the pair of mounting pins to rest upon the surface of the boss.

46. (Original) An electrical junction box having plural walls cooperatively arranged and interconnected so as to substantially bound a volume and to define an opening to said volume by which electrical components and electrical wiring may pass into and from said volume; a back one of said plural walls outwardly and at respective corners of the junction box defining
5 respective ones of plural corner recesses, each corner recess including a recess floor bounded by a pair of recess side walls which intersect with the floor and with each other at substantially a right angle, and a locating member centrally located of each of said plural corner recesses and projecting upwardly in this recess perpendicularly to the back wall.

47. (Original) The electrical junction box of Claim 46 wherein said locating member is configured as a pin member round in cross section, and providing for receipt into said corner recess of a mounting member in a selected one of plural alternative orientations.

48. (Currently amended) An electrical junction box having plural walls cooperatively arranged and interconnected so as to substantially bound a volume and to define an opening to said volume by which electrical components and electrical wiring may pass into and from said volume; a back one of said plural walls outwardly and at respective corners of the
5 junction box defining respective ones of plural corner recesses, each corner recess including a recess floor bounded by a pair of recess side walls which intersect with the floor and with each

other at substantially a right angle, and a locating member centrally located of each of said plural corner recesses and projecting upwardly in this recess perpendicularly to the back wall;

wherein said locating member is configured as a pin member round in cross section, and
10 providing for receipt into said corner recess of a mounting member in a selected one of plural
alternative orientations; ~~The electrical junction box of Claim 47~~

wherein said mounting member includes an elongate tab member received into a corner
recess and upon said mounting pin, said tab member defining a locating hole received over said
mounting pin, and plural end edge surfaces disposed about said locating hole and which intersect
15 at 45 degree angles to one another and to the length of said elongate mounting tab, whereby said
mounting tab may be adhesively secured into said corner recess in any one of three alternative
positions each disposed at 45 degrees to the other, and said mounting tab may extend outwardly
of said junction box to provide for fastening of said junction box to underlying structure.

49. (Original) A mounting tabs providing for adhesive installation into a recesses of a
junction box, said mounting tab being elongate and including three end edge surfaces each
disposed at an effective angle of 45 degrees relative to the adjacent end edge surface.

50. (Original) A method of mounting an electrical junction box, said junction box having
plural walls cooperatively arranged and interconnected so as to substantially bound a volume and
to define an opening to said volume by which electrical components and electrical wiring may
pass into and from said volume; said method including steps of:

5 providing at a back one of said plural walls of said junction box and at respective corners
thereof respective ones of plural corner recesses, configuring each corner recess to include a
recess floor bounded by a pair of recess side walls which intersect with the floor and with each
other at substantially a right angle, and providing a locating member centrally located of each of
said plural corner recesses and projecting upwardly in this recess perpendicularly to the back
10 wall.

51. (Original) The method of Claim 50 further including steps of configuring said
locating member as a pin member round in cross section, and providing for receipt into said
corner recess of a mounting member in a selected one of plural alternative orientations.

52. (Currently amended) A method of mounting an electrical junction box, said junction box having plural walls cooperatively arranged and interconnected so as to substantially bound a volume and to define an opening to said volume by which electrical components and electrical wiring may pass into and from said volume; said method including steps of:

providing at a back one of said plural walls of said junction box and at respective corners thereof respective ones of plural corner recesses, configuring each corner recess to include a recess floor bounded by a pair of recess side walls which intersect with the floor and with each other at substantially a right angle, and providing a locating member centrally located of each of said plural corner recesses and projecting upwardly in this recess perpendicularly to the back wall;

further including steps of configuring said locating member as a pin member round in cross section, and providing for receipt into said corner recess of a mounting member in a selected one of plural alternative orientations; ~~The method of Claim 51~~

further including steps of providing a mounting member configured as an elongate tab member which is received into a corner recess and upon said mounting pin, providing for said tab member to define a locating hole received over said mounting pin, and providing said tab member with plural end edge surfaces disposed about said locating hole and which intersect at 45 degree angles to one another and to the length of said elongate mounting tab, whereby said mounting tab may be adhesively secured into said corner recess in any one of three alternative positions each disposed at 45 degrees to the other, and said mounting tab extends outwardly of said junction box to provide for fastening of said junction box to underlying structure.